










SCAN SHEET FOR UNITEC MODEL MS210

Unicorn WorkFlows

| | |
|--|---|
| <p>I. In your Workflows client choose "Preference/Peripherals/Barcode Reader...". Check the "Barcode reader available" checkbox Port information: Select the radio button for "Attached to keyboard or USB" Set the Barcode settings to: Preamble: 27 66 Postamble: 27 68</p> | <p>II. In your Workflows client choose "Preference/Peripherals/Barcode Configuration...". For the "Barcode #1" tab the settings are: Read length: 14 Skip length: 0 Use length: 14 Checksum box is checked. Other two boxes are NOT checked.</p> |
|--|---|

Scan the barcodes below, left to right and top to bottom to configure your scanner.

| | | | | | | |
|--|--|---|--|--|--|--|
| <p>Group 1</p>  <p>1</p> | | <p>DEFAULT</p>  <p>F F</p> | | <p>EXIT</p>  <p>E E</p> | | <p>Group 5</p>  <p>5</p> |
| <p>PREAMBLE</p>  <p>P P</p> | | <p>ESC</p>  <p>% A</p> | | <p>B</p>  <p>B</p> | | <p>PREAMBLE</p>  <p>P P</p> |
| <p>POSTAMBLE</p>  <p>O O</p> | | <p>ESC</p>  <p>% A</p> | | <p>D</p>  <p>D</p> | | <p>POSTAMBLE</p>  <p>O O</p> |
| <p>Terminator</p>  <p>D 1</p> | | | <p>No CR</p>  <p>3</p> | | | <p>EXIT</p>  <p>E E</p> |
| <p>Group 8</p>  <p>8</p> | | | <p>Codabar</p>  <p>G 5</p> | | | <p>Enable</p>  <p>1</p> |
| | | <p>Enable</p>  <p>3</p> | | | <p>EXIT</p>  <p>E E</p> | |